



TriCIS TS-586dn-A Enterprise Printer

Designed to meet SDIP 27/2 Level A (UK CFTCS)

TS-586dn-A



Enterprise productivity at unmatched speeds.

The TriCIS TEMPEST Level A modified version of the HP PageWide Enterprise 586dn Multifunction Colour Duplex A4 Printer (print, scan and copy) provides ultimate value for today's enterprises.


Using HP PageWide Technology, it delivers the fastest speeds and deepest security for the lowest total cost of ownership in its class. It has power productivity with seamless workflow features. It is lightweight with embedded HP Proximity Card Reader.

Designed to meet TEMPEST SDIP 27/2 Level A (UK CFTCS)

Key Features

- Provides Print, Copy and Scanning functionality and a Colour Graphics Display (CGD) with touchscreen
- Fibre Ethernet LAN Port 100Base-FX (or Gigabit option) over ST or SC Connectors.
- HP Access Control Secure Authentication / Secure Pull Printing allows printing only when the user authenticates locally at the printer by using HP proximity card readers or PIC/PIN codes.

Product Specification

All-In-One functions:	Print, copy, scan
Print technology:	HP PageWide Inkjet Technology with pigmented inks
Print speed:	Black (Professional mode, A4): Up to 50 ppm Black (General Office mode, A4): Up to 75 ppm Colour (Professional mode, A4): Up to 50 ppm Colour (General Office mode, A4): Up to 75 ppm Black Duplex (A4): Up to 38 ipm Colour Duplex (A4): Up to 25 ipm
Scan Resolution:	Enhanced: Up to 600 dpi; Hardware: Up to 600 x 600 dpi; Optical: Up to 600 dpi
Scan Speed (two sided):	Normal, A4: Up to 45 ppm/70 ipm (b&w), up to 45 ppm/70 ipm (colour)
Copy Resolution:	Black (text & graphics): Up to 600 x 600 dpi (flatbed), 600 x 450 dpi (ADF) Colour (text & graphics): Up to 600 x 600 dpi (Flatbed), 300 x 600 dpi (ADF)
Copy Speed:	Black (laser comparable): Up to 50 cpm Colour (laser comparable): Up to 50 cpm
Connectivity:	Fibre Ethernet LAN Port 100Base-FX (Gigabit option) over ST or SC Connectors. No RJ45 Ethernet No Bluetooth No Air Print No Wi-Fi No NFC
Access Control: Universal Proximity Card Reader	Control printing access by requiring users to authenticate at your imaging and printing devices Integrated HP reader
Trusted Platform Module	 The HP Trusted Platform Module Accessory strengthens protection of encrypted credentials and data stored on the printer or MFP by automatically sealing device encryption keys to the TPM.[1]

Supported network protocols:	IPv4/IPv6: Apple Bonjour Compatible (Mac OS v10.2.4 or higher), SNMPv1/v2c/v3 HTTP, HTTPS FTP, TFTP, Port 9100 LPD, WS Discovery IPP, Secure-IPP IPsec/Firewall; IPv6: DHCPv6, MLDv1 ICMPv6; IPv4: Auto-IP SLP, Telnet IGMPv2, BOOTP/DHCP WINS, IP Direct Mode, WS Print
Physical Specifications:	Height: 529mm Width: 530mm Depth: 564mm
Power:	100-240VAC 50-60 Hz Max Power: 62W Standby Power: 8.5W UK mains cable and plug
Weight	32.3kg
Temperature range:	Operating temperature and humidity: Ambient temperature: 0 to 35°C Relative humidity (RH): 10 to 90% Storage and transport temperature at RH 10 to 90% (noncondensing): -20 to 60°C
Warranty:	One-year, return to factory.



Any images used are for illustrative purposes only and is subject to change. Any information discerned from the image pertaining to the product may not reflect the final completed version or newest iteration.